

25,000 Mile Maintenance Guide

<i>Maintenance Item</i>	<i>Recommended</i>		<i>Actual I/R & Date</i>	<i>Brand Used</i>	<i>Warranty Period</i>
	<i>Inspect</i>	<i>Replace</i>			
<i>Example-Battery</i>		X	R 11/5/02	AC Delco	5 yrs
<i>Battery</i>	X				
<i>Differential</i>	X				
<i>Fuel Filter</i>		X			
<i>Engine Oil</i>	X	X			
<i>Power Steering Fluid</i>	X				
<i>Tires*</i>	X				
<i>Transmission Fluid</i>		X			
<i>Wiper Blades</i>	X	X			
<i>Washer Fluid</i>	X				
<i>Exterior Care</i>	X				
<i>Dist Cap / Ignition Rotor</i>	X				

* Tires should also be rotated and balanced every 15,000 miles.

Vehicle:

Performed by:

Cost:

Owner's Notes:

Shop's Notes:

(items noted during vehicle inspection, repairs needed, etc.)

Maintenance guide courtesy of www.trustmymechanic.com. This schedule is a general guide for most cars and trucks. It does not replace your specific manufacturer's maintenance recommendations. This schedule is meant to be a helpful way for you and your repair shop to perform needed maintenance and build a repair history log.

Explanations and Recommendations

Battery - Check terminals and cables--loose or dirty battery cables are a common "no start" condition. Cable ends and battery terminals should be cleaned with a wire brush and light sand paper periodically to remove any corrosion build up. Caution: remove all metal objects like wrist watches and rings before working around a battery—a spark or fire can occur.

Battery Load - Battery "load" is how much load or drain can be placed on the electrical system before the battery begins to discharge itself. Think of it as how much electricity the battery can store before having to be recharged. It is not uncommon for batteries to go completely "flat" or discharged without ever giving a warning signal to the operator. Have the mechanic check the battery condition and **load levels at every oil change interval if the battery is over 2 years old** to ensure the battery will not leave you unexpectedly stranded.

A weak battery that is not storing enough power will cause the alternator to work harder and possibly cause premature alternator failure. Dirty or corroded battery terminals can severely reduce the lifespan of the battery and alternator. A quick and inexpensive battery check and cable inspection can be done at each oil change.

The replacement battery should be the same size, have the same battery cable connections, and should be the same electrical capacity as the original battery. To learn more about automotive batteries, go to www.acdelco.com. We recommend ACDelco as our premium replacement battery supplier.

Differential Fluid – (A rear differential is only found on rear wheel drive cars and trucks.)

Inspect: The rear differential (commonly referred to as the rear end) fluid or grease should be checked during each routine oil change and topped off as needed with the fluid prescribed in the owner's manual.

Replace: Drain and flush the rear end fluid periodically to remove any metal filings that have normally accumulated in the differential housing. Replace the differential cover gasket and add any recommended supplemental additive prescribed in the owner's manual.

Fuel Filter - Fuel filters become clogged with dirt and debris during normal operation and should be replaced to increase performance, extend fuel pump life, and aid in fuel economy.

Engine Oil -

Inspect: Check oil level when engine is cold and with vehicle on level ground.

Replace: Change oil and filter. Check all fluids, tires and air pressure, air filter, belts and hoses and spare tire condition when changing the engine oil. This is also a great time to clean the corrosion from the battery cables.

Power Steering Fluid –

Inspect: Check level. Power steering fluid can either be pink or clear in color, usually only a very small amount is needed to top off fluid level. If more than 2 oz. is needed, have the system checked for leaks or wear.

Replace: Power steering fluid just like any other fluid becomes dirty and contaminated and should be replaced with clean fluid periodically. Dirty power steering fluid can cause the power steering pump or the power steering gear assemblies to fail and can cause premature wear to occur.

Tires --

Inspect: Check pressure and tread wear. Check air pressure cold unless otherwise described in the owner's manual. Inspect tires for uneven tread wear, punctures, bulges, or cuts in sidewall of the tire.

Rotate and balance: Routine rotation and balancing can greatly extend the life of your tires. Most front end "shake and shimmy" complaints can be attributed to out of balance, or out of round tires. Ask your mechanic to inspect the brakes for free when rotating and balance tires.

Transmission Fluid (automatic transmission) -

Inspect: Usually the transmission fluid level is checked with the engine hot and in park, and with engine running. Check your owner's manual for proper fluid type and proper fluid level inspection procedures. Automatic transmission fluid is usually pink in color. Most standard shift transmissions will have a drain plug to service the fluid. Some stick shift transmissions use engine oil as a lubricant; consult your owner's manual when servicing. It could also be a good idea to have the replacement fluid type information available for the repair shop.

Replace: Consult vehicle owner manual for proper fluid type and service interval. If applicable, replace the internal automatic transmission filter or clean the re-usable screen when changing the transmission fluid. A transmission pan gasket will also be required during a filter change. Some newer model vehicles require special additives and detergents be used—consult owner's manual for fluid specifications.

Windshield Wipers --

Inspect: Check wiper blades for wear and washer fluid level during a regular oil and filter change. Don't make the mistake of never thinking about replacing or inspecting the wiper blades until you really need them.

Replace: Some wiper blades are different lengths for driver and passenger side. Measure old blades before replacing with new ones. Some manufactures like Anco offer different replacement wiper blade types (i.e. for snow and ice, off road, and severe duty).

Windshield Washer Fluid - Check level. Anti-freezing and water repelling additives can also be added to the washer fluid reservoir. Not only will washer fluid aid in removing dirt from the windshield, but also it will act as a lubricant to

prolong the life of the wiper blade. Adding rubbing alcohol to the washer fluid can be harmful to the rubber on the wiper blades.

Exterior Care- There are all types of automotive finish waxes on the market, find one that is right for your vehicle surface and your pocket book. Some waxes are expensive and time consuming to apply, and may or may not be worth the extra expense and effort. A visit to a detail shop might be well worth the additional expense to obtain a professional long lasting waxed finish, or at least some advice or a product recommendation.

Distributor Cap/Ignition Rotor – These items should be inspected/replaced when replacing spark plugs and spark plug wires, or when a “major tune-up” is called for. The distributor cap is where the other end of the spark plug wires connect to, and the ignition rotor is underneath the distributor cap. Some newer model vehicles do not have a distributor at all. These cars are designed with Distributorless Ignition Systems (D.I.S.), and therefore do not have these parts.